

PENS SAFETM

INC.
S T R E N G T H & S E C U R I T Y

Pensafe Inc.
Unit 4, 1175 Barton Street
Stoney Creek, Ontario, Canada
L8E 5H1
Phone (Toll Free): 1-866-212-2211
Phone: 905-643-7188
Fax: 905-643-5088
Website: www.pensafe.ca

Certificate of Test

DEIMOS INC

Packing Slip: 7350

Ship Date: 3/06/18

Part Number: 3220-11-0-00-11-1
Customer Part Number: N/A
Part Description: ring d single slot 1-3/4" clear chromate
Heat Code: 17A

Material: CARBON STEEL
Specification: Certified to ANSI Z359.12-2009 & CSA Z259.12-16
Minimum Tensile Load (lbs): 5000
Minimum Gate Load (lbs) N/A
Minimum Side Load (lbs): N/A
Hardness: 35-42 R.C.
Corrosion Resistance: Minimum 96 HR Salt Spray
Remarks: 100% Proof Loaded to 3600 LBS
Note: Chemical Analysis available upon request.

The customer, including but not limited to Product Distributors and OEM manufacturers, agree and acknowledge that it is solely responsible for conveying to its customers and/or end users, warnings and information concerning the use of the Product including but not limited to: the dangers associated with part usage compatibility, improper connection, accidental barrel disengagement, accidental disengagement, gate face loading, accidental lock-lever deactivation, connector tip loading, deliberate lock lever deactivation, multiple loading and cleaning and usage. The customer shall hold Pensafe harmless from and indemnify PenSafe against any and all claims, demands and actions based upon or arising out of any activities performed by PenSafe and its employees and agents pursuant to this shipment and shall, at the request of PenSafe, defend any and all actions brought against PenSafe based upon any such claims or demands.

We hereby certify that the results in the attached documents are correct to the best of our knowledge as contained in the company records.

Tony Stanges

Product Integrity Dept

PENS SAFETM
INC.
S T R E N G T H & S E C U R I T Y