

# **PENSAFE**<sup>TM</sup> INC.

**S T R E N G T H   &   S E C U R I T Y**

Packing Slip: 1,576

Ship Date: 2/19/15

## **Certificate of Test**

To: DEIMOS INC  
Part Number: 3221-12-0-00-11-1  
Part Description: ring D bent single slot 1-3/4" yellow dichromate  
Customer Part Number:  
Heat Code: 14D, E

---

Material: CARBON STEEL  
Specification: Certified to ANSI Z359.12-2009 & CSA Z259.12.01  
Minimum Tensile Load (lbs): 5000  
Minimum Gate Load (lbs) N/A  
Minimum Side Load (lbs): N/A  
Hardness: 35-42 R.C.  
Corrosion Resistance: Minimum 50 HR Salt Spray  
Remarks: 100% Proof Loaded to 3600 LBS  
Note: Chemical Analysis available upon request.

---

The customer, including but not limited to Product Distributors and OEM manufacturers, agree and acknowledge that it is solely responsible for conveying to its customers and/or end users, warnings and information concerning the use of the Product including but not limited to: the dangers associated with part usage compatibility, improper connection, accidental barrel disengagement, accidental disengagement, gate face loading, accidental lock-lever deactivation, connector tip loading, deliberate lock lever deactivation, multiple loading and cleaning and usage. The customer shall hold Pensafe harmless from and indemnify PenSafe against any and all claims, demands and actions based upon or arising out of any activities performed by PenSafe and its employees and agents pursuant to this shipment and shall, at the request of PenSafe, defend any and all actions brought against PenSafe based upon any such claims or demands.

We hereby certify that the results in the attached documents are correct to the best of our knowledge as contained in the company records.

Product Integrity Dept

**PENSAFE**<sup>TM</sup>  
INC.  
**S T R E N G T H   &   S E C U R I T Y**